

Stagionatura — STX 1400 PV BK

Dry aging and seasoning



Technical data

Gross volume	1355 lt
Working temperature	+6+30 °C
Humidity range	40%-90%
Motor type	Plug-in
Refrigerant	R452A
Refrigeration power	1319 W (-10°C / +45°C)
Absorption	3281 W
Voltage/Frequency	230V/1~/50Hz

Refrigeration details

Refrigeration unit	Tropicalized condensing unit
Refrigerant charge	1400 gr
Evaporator	With cataphoresis anti-corrosion treatment
Defrost	Automatic by electric heater
Condensate evaporation	Through easy extractable condensation collector tray (for installations without water drain system)

Construction details

Product dimensions WxDxH	1435x870x2085
Packaging dimensions WxDxH	1500x910x2195
Gross weight	223 Kg
Structure	Stainless steel AISI 304 monocoque
External/Internal material	Inside and outside in stainless steel AISI 304; internal motor unit compartment, external backside and external bottom in colaminated steel
Insulation thickness	60 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP)
Inner corners	Rounded for an easy cleaning
Door	2 Self-closing glass doors with 105° door stop
Door gasket	Magnetic and removable, designed to improve insulation and to reduce energy consumption
Feet	In AISI 304 stainless steel, height adjustable (90mm-125mm)

Functions

Control panel	7" touch screen graphic display
Functions	Manual drying and seasoning cycles configurable in duration, temperature, humidity and ventilation. Automatic cycles up to 21 phases, work break included. Automatic air exchange cycle. 20 customizable programs. HACCP alarms
Languages	Italian, English, Flemish, French, German, Spanish
Connection	As standard: Remote access through serial interface. Via Web it is possible to monitor HACCP traceability, appliance operation and parameters. Graphic and as pdf file export of registered data. Email sending of alarms notification

Accessories

Lighting	As standard
Lock	As standard
No. included accessories	4 - Pair of stainless steel runners with no. 5 aluminium hanging bars for cured meat

Versions

Versions	Power supply frequency 60Hz
----------	-----------------------------